



LangID NSK NUP319EM NUP-Type

Bearing No. NUP319EM

NUP319EM Bearing 2D drawings and 3D CAD models

Size	95x200x45 mm
Bore Diameter	95 mm
Outer Diameter	200 mm
Width	45 mm
d	95 mm
Fw	121,5 mm
D	200 mm
B	45 mm
C	45 mm
r min.	3 mm
r1 min.	3 mm
da min.	108 mm
Da max.	187 mm
db max.	118 mm
db min	108 mm
ra max.	2,5 mm
rb max.	2,5 mm
S	1,5 mm
Db max	187 mm
Weight	7,13 Kg
Basic dynamic load rating (C)	335 kN
Basic static load rating (C0)	385 kN
(Grease) Lubrication Speed	3000 r/min
hidYobi	NUP319EM
LangID	1
D_	200



Win-Win Industrial Part Co.,Ltd

Macha rpm	6000
B_	45
hidTable	ecat_NSCLDR
Oil rpm	3600
rb	2.5
mass	7.38
GRS rpm	3000
ra	2.5
db max	118
TSR rpm	3800
C0	385
DE_	177.5
Prod_Type3	CRB_SR_NUP
da	108
DA_	28
Z_	14
D_a max	187
yobi	NUP319EM
dd min	134
C_conv	335000
ALPHA_	0
SDM_	149.5
r	3
dc min	124
KBRG	4165
SBRG	3
r1	3
DI_	121.5